



HCS
HC SERVICES
FIRE PROTECTION



Model 600 K
150 LB. HALON 1211
WHEELED FIRE EXTINGUISHER

- Brass, chrome plated operating valve
- 200 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Quick release 50 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyurethane paint finish
- Large color coded mylar instruction labels
- Operating temperature range: -65° to +120° F.

SPECIFICATIONS	150 LB. HALON 1211
Model Number	600
Agent	Halon 1211
U/L Rating	30A:240B:C
Capacity (lbs./kg.)	150 / 68
Shipping Weight (lb./ kg)	
Discharge Time (sec.)	48
Cylinder - DOT 4BW240	
Operating Pressure	200 / 1380
Test Pressure	480 / 3312
Burst Pressure (Minimum)	960 / 6624
(psi/kPa)	
Discharge Range (ft/ m)	30 - 40 / 9.1 - 12.2
Operating Temp. Range (F/ C)	-65° to +120° / -54° to +49°
Safety Disc Burst Range (psi/ kPa)	400 - 500 / 2760 - 3450
Hose Length (ft./ m)	50 / 15.2
Hose Diameter (in./ cm)	.75 / 1.90
Wheels (Semi-pneumatic) (in./ cm)	16 x 4 / 40.64 x 10.16
Height (in./ cm)	59 / 150.0
Width (in./ cm)	29 / 73.7
Depth (in./ cm)	42 / 106.7

HC Services, INC
1455 West Drive Laurel, MS 39440
Phone:601-649-0888 Fax:601-649-0897
sales@int-fire.com www.int-fire.com